

2EHUÀ IFKHQYDULDQWHQ

Stern „schwarz“

SROLHUWHV VHLGHQJOIQ]HQG DQRGLVLHUWHV)HOJHQEHWW)HOJHQVWHUQ
YRQ +DQG VFKZDU] PDWW ODFNLHUW

Stern „silber“

SROLHUWHV VHLGHQJOIQ]HQG DQRGLVLHUWHV)HOJHQEHWW XQG)HOJHQVWHUQ
7HLOEHUHLFKH YRQ +DQG VFKZDU] PDWW ODFNLHUW

Rad „natur“

SROLHUWHV VHLGHQJOIQ]HQG DQRGLVLHUWHV 5DG)HOJHQEHWW XQG
)HOJHQVWHUQ %DVLVREHUÀ IFKH]XQ /DFNLHUHQ LQ :XQVFKIDUEH
/DFNLHUXQJ LVW QLFKW LP 2772)8&+0000/HLVWXQJVVSHNWUXP

enthalten!)

Surface diversity:

Spokes “black“

polished, silk-gloss anodised outboard rim; disc base and rim
star hand-painted in matt black

Spokes „silver“

polished, silk-gloss anodised outboard rim and rim star, disc
base hand-painted in matt black

Wheel “nature“

polished, silk-gloss anodised wheel (outboard rim, disc base and
rim star) - basis surface for painting in car colour
(Painting is not included in the OTTO FUCHS scope of service!)

17“

18“

19“

Verwendungsbereich/Application Area
Porsche 987

OTTO FUCHS KG

Derschlager Straße 26
58540 Meinerzhagen, Germany

Fuchsfelgen-Hotline +49 2354 73-317
fuchsfelge@otto-fuchs.com
www.fuchsfelge.com

)•U HYWO)HKOHU EHL WHFKQ \$QJDEHQ •EHUQHKKPHQ ZI U NHLOH *HZIKU .UUV•PHU YRUEHKKOYV]HURUW] [FHSWGG
: H GR QRW DFFHSW OLDELQW\ IRU DQ\ SRVV PLVWDNH\ / LQ WKK WHFKQLFDO VSHFLJ FDWLRQ\ FURUW]HURUW] [FHSWGG

'LH DNWXHOHQ 9HUZHQG XQJVEHUHLFKH ; QGHQ 6LppL BQD L RGH X Q W H U H D online at
www.fuchsfelge.com. www.fuchsfelge.com.

Typ 987

³)XFKVIHOJHQ

9RUGHUDFK V H (7 _ NJ _ ¼
5HLIHQJU | % H = 5
(LQ]HODEQDKPH JHP I % † †

+LQWHUDFK V H (7 _ NJ _ ¼
5HLIHQJU | % H = 5
(LQ]HODEQDKPH JHP I % † †

+LQZHUVLJLQDO 3RUVFKHJU | % H - [

³)XFKVIHOJHQ

9RUGHUDFK V H (7 _ NJ _ ¼
5HLIHQJU | % H = 5
(LQ]HODEQDKPH JHP I % † †

+LQWHUDFK V H (7 _ NJ _ ¼
5HLIHQJU | % H = 5 RGHU
mind. 20 mm Distanzscheibe erforderlich
(LQ]HODEQDKPH JHP I % † †

³)XFKVIHOJHQ

9RUGHUDFK V H [(7 _ NJ _ ¼
5HLIHQJU | % H = 5
(LQ]HODEQDKPH JHP I % † †

+LQZHUV RSWLVFKHQ *U•QGHQ PP 'LVWDQ]VFKHLEH HUIRUGHUOLFK QXUNPELQHUEDU PLW = 5 0LFKHOLQ 6SRUW 36 1 (LQH DXVUHL = 5 0LFKHOLQ 6SRUW 36 1
SIRKOHQ QXU NRPELQLHUEDU PLW = 5 0LFKHOLQ 6SRUW 36 1 (LQH DXVUHL = 5 0LFKHOLQ 6SRUW 36 1
Sport PS2 N2

+LQWHUDFK V H (7 _ NJ _ ¼
5HLIHQJU | % H = 5
(LQ]HODEQDKPH JHP I % † †

+LQZHLVPP 'LVWDQ]VFKHLEH HUIRUGHUOLFK QXUNPELQHUEDU PLW = 5 0LFKHOLQ 6SRUW 36 1 (LQH DXVUHL = 5 0LFKHOLQ 6SRUW 36 1
FKHQGH 5HLIHQDEGHFNXQJ LVW VLFKHU]X VWHOORFK PWHN QXVURGL ; FDWLRQV D KH H O
NDQQ 0RGL ; NDWLRQH Q DP KLQWHUHQ 5DGODXI HUIRUGHUOLFK

Type 987

17" Fuchsfelgen:

Front: 7J x 17, ET55 | 7.50 kg | € 559,-*
tyre size: 205/55ZR17

6W9=2 HUIRUGHUOLFK Special approval acc. to §§21, 19.3 StVZO necessary

Rear: 8J x 17, ET52 | 7.70 kg | € 589,-*
tyre size: 235/50ZR17

6W9=2 HUIRUGHUOLFK Special approval acc. to §§21, 19.3 StVZO necessary

(7 Advice: original Porsche size 8J x 17, ET40

18" Fuchsfelgen:

Front: 8J x 18, ET52 | 8.20 kg | € 669,-*
tyre size: 235/40ZR18

6W9=2 HUIRUGHUOLFK Special approval acc. to §§21, 19.3 StVZO necessary

Rear: 10J x 18, ET65 | 8.80 kg | € 719,-*
tyre size: 265/40ZR18 or 265/35ZR18
20 mm spacer required at least

6W9=2 HUIRUGHUOLFK Special approval acc. to §§21, 19.3 StVZO necessary

19" Fuchsfelgen:

Front: 8½J x 19, ET56 | 10.50 kg | € 949,-*
tyre size: 235/35ZR19

6W9=2 HUIRUGHUOLFK Special approval acc. to §§21, 19.3 StVZO necessary

For technical reasons 7 mm spacer recommended
only in combination with 235/35ZR19 Michelin
Sport PS2 N2

Rear: 11J x 19, ET51 | 11.50 kg | € 999,-*
tyre size: 295/30ZR19

6W9=2 HUIRUGHUOLFK Special approval acc. to §§21, 19.3 StVZO necessary

Advice: EBC optional required, only in combination with

Uuedu PLW = 5 0LFKHOLQ 6SRUW 36 1 (LQH DXVUHL = 5 0LFKHOLQ 6SRUW 36 1
FKHQGH 5HLIHQDEGHFNXQJ LVW VLFKHU]X VWHOORFK PWHN QXVURGL ; FDWLRQV D KH H O
NDQQ 0RGL ; NDWLRQH Q DP KLQWHUHQ 5DGODXI HUIRUGHUOLFK

(&(5

)XFKVIHOJHQ GLH JHP I % GHU (&(5 5HJHOXQJ YRP
den in den Fahrzeugpapieren eingetragenen Reifendimensionen sowie der original
Radschrauben auf dem Fahrzeug montiert sind, müssen nicht in die Fahrzeugpa-
piere eingetragen werden.

†† 6W9=2

:LUG YRQ GHP LQ GHU *HQHKPLJXQJ JHQDQQWHQ 9HUZHQG XQJVEHUHLFKH ; QGHQ 6LppL BQD L RGH X Q W H U H D
VR LVW HLQH (LQ]HODEQDKPH JHP I % † † XQG 6W9=2 HUIRUGHUOLFK Special approval

ECE R124

The ECE R124 label is required in the car documents provided the tyre dimensions are the same as listed in the car documents and the original bolts are used.

§§21, 19.3 StVZO

9HUZHQG XQJVEHUHLFKH ; QGHQ 6LppL BQD L RGH X Q W H U H D on a special approval
6W9=2 HUIRUGHUOLFK Special approval